ROAD OPTIMIZED INNOVATIONS

SMARTVALVE®

RETROFIT ORDERING GUIDE

Start

H00700PK
Note: H00700PK is required for the installation process.
The tool is required to set the ride, over-height, and dump height for the SmartValve.

J1939 CanBus
Note: 250 Kilobit per second (kb/s) is required for the auto-return to ride height safety feature. Some OEMs have updated to 500kb/s speed and eliminated 250 kb/s. If tractor is equipped with only 500kb/s network: H00701SDC is required

Note: J1939 became standard in 2006. SmartValve is not compatible with tractors manufactured before 2006.

What type of drivetrain is it on?

6x4
4x2

Is there anything unusual about the tractor?
i.e. Extended frame, dual height control valves, triple drive axle, etc.

Yes

Please contact Link Mfg.
800-222-6283

No

Is the tractor equipped with a OEM switch controlled dump/exhaust feature?

6x2 Non-liftable tag configuration

Yes	No	
Freightliner / Western Star H00700R1A	Freightliner / Western Star H00700R21A	Freightliner H00700R41A
Kenworth H00700R2A	Kenworth H00700R22A	Kenworth Not Configured
International Motors H00700R3A	International Motors H00700R23A	International Motors H00700R43A
Peterbilt H00700R4A	Peterbilt H00700R24A	Peterbilt H00700R44A
Volvo H00700R5A	Volvo H00700R25A	Volvo Not Configured
Mack H00700R6A	Mack H00700R26A	Mack Not Configured